




K 系列截止型电磁阀气控阀 (二位五通)
K Series 5/2 Solenoid Stop Valve



订购码
Ordering code

K25J	D	-	8
<p>规格 K 系列二位五通截止式气动换向阀 Specification K series 5/2 way solenoid stop valve</p>	<p>控制方式 D:单电控 Q:单气控 Control methods D:Single electronic control K:Single electronic control</p>		<p>接管口径 Port size 6:G1/8" 8:G1/4" 10:G3/8" 15:G1/2" 20:G3/4" 25:G1"</p>

符号
Symbol



规格
Specifications

参数 Parameter	订购码 Ordering code	K25JD-6 K25JQ-6	K25JD-8 K25JQ-8	K25JD-10 K25JQ-10	K25JD-15 K25JQ-15	K25JD-20 K25JQ-20	K25JD-25 K25JQ-25
公称通径 mm Nominal diameter		6	8	10	15	20	25
工作压力范围 Mpa Working pressure range		0.15~0.8					
泄漏量 cm ³ /min Leakage rate		≤10			≤25		≤50
换向时间 S Reversing time		≤0.06			≤0.08		≤0.12
换向频率 Hz Commutating frequency		≥10			≥8		≥5
环境温度 °C Ambient temperature		-10~55					
介质温度 °C Fluid temperature		-5~50					
流通能力 S值mm ³ Negotiability		≥10	≥20	≥40	≥60	≥120	≥190
电源电压 V Power consumption		AC:220,110,36 DC:48,24,12 电压被动允许为额定值的+10%--15%气控无本项参数 AC:220,110,36 DC:48,24,12 Voltage is allowed to set as rated voltage+10%--15%Null parameter in pneumatics					
控制压力 Mpa Pressure control		≥0.2					
寿命 千次 / Thousands Life		≥1500					